

**Item No. 213069 - Monitor Mount for Thumb Screw Attachment**

**ProClip®**  
Installation Instructions

**Compatible with:**

ProClip All Monitors with thumbscrew holes



**Warnings:**

Carefully read all instructions and review the images before attaching.

**Do not** attach anything to the mount until after attaching the mount to the dashboard. Doing so makes it more difficult to attach the mount to the dash. **Please note:** If you screw into the mount it will be considered used and therefore non-refundable.

The ProClip mount and/or holder in the installation pictures may look slightly different from the one you have received. However, the same instructions apply. If you have questions call our customer service at **1-800-296-3212** or **+1-847-388-7171**.

ProClip USA, Inc. may not be held liable for any personal injury or damage to a vehicle or device, resulting from accident or improper use or installation, before, during or after the installation or removal of this mount and/or holder.



1. Unscrew the screw in the center of the Monitor Mount and remove the Monitor Mount from the Tilt Swivel base plate. Place the Tilt Swivel base plate over the matching holes in your mounting bracket (ProClip mount shown in picture)



2. Attach the base plate by using the applicable screws enclosed – self-tapping screws if the mount has small holes or machine screws with nuts if the mount is made of metal and has large holes.



3. Place the Monitor Mount onto the Tilt Swivel base plate and attach it with the center screw. This screw also controls the pivot, tighter for a firm hold and loose for more (easier) movement/angling of the holder.



4. The Monitor Mount in place. Place your Monitor into the Monitor Mount and tighten the thumbscrew at the bottom to secure the monitor.